



제품별 설치사이즈 - 보일러(형형)

MODEL			UNIT	CIH-20	CIH-30	CIH-40	CIH-50	CIH-60	CIH-80	CIH-100	CIH-120	CIH-150	CIH-180	CIH-200	CIH-250	CIH-300
HEAT CAPACITY			kcal/hr	200,000	300,000	400,000	500,000	600,000	800,000	1,000,000	1,200,000	1,500,000	1,800,000	2,000,000	2,500,000	3,000,000
FUEL USAGE	LNG	10,500kcal/Nm ³	Nm ³ /Hr	22.4	33.6	44.8	56.0	67.2	89.6	112.0	134.5	168.1	201.7	224.1	280.1	336.1
	L.O	10,200kcal/Kg	Kg/Hr	23.1	34.6	46.1	57.7	69.2	92.3	115.3	138.4	173.0	207.6	230.7	288.4	346.0
DIMENSION	HEATER BODY & SKID	A	mm	1865	2097	2113	2161	2314	2520	2527	2604	2791	2900	2971	3265	3403
		B	mm	1460	1463	1463	1511	1717	1870	1881	1954	2150	2252	2321	2654	2653
		C	mm	1065	1070	1136	1172	1328	1460	1544	1608	1792	1894	1962	2172	2266
		D	mm	1943	1963	2217	2503	2642	3024	3332	3677	3972	4331	4448	4970	5462
		E	mm	2416	2436	2744	3073	3212	3788	4096	4441	4763	5795	5393	5915	6411
	HEATER ROOM	F	mm	4081	4100	4480	4845	4140	5848	6240	6649	7128	7589	8000	8687	9277
		G	mm	3865	4097	4113	4161	4314	4520	4527	4604	4791	4900	4971	5256	5403
APPROX. WEIGHT			Ton	1.9	2.0	2.2	2.5	3.0	3.5	3.8	4.3	5.4	6.0	6.7	9.8	12.2
OIL CHARGE AMOUNT			Liter	180	200	250	300	350	530	650	770	1,150	1,400	1,600	2,500	3,000

* 상기사양은 고객요구 및 품질향상을 위해 예고없이 변동될수 있습니다.

